



## DESCRIPTION

**Material:** It is manufactured from ALUTEX-A12 as the basic pipe, thermal insulation of mineral wool 25 mm thick and external jacket formed from polyester laminated aluminium foil. Due to its exceptional flexibility it is easy to install on circular and oval connectors.

**Application:** IZOTEX-A12 is lightweight, flexible, thermally insulated pipe designed for the installation into the ventilation and air conditioning systems.

🔥 **Application temperature:** -30°C to +140°C

🔄 **Diameters:** 82 mm to 508mm

➔ **Manufacturing lengths:** 10m

✳️ **Operating pressure :** max.permissible to 2500 Pa

🌬️ **Max.air velocity:** 30m/s

# **Ident:** C05+diameter

Internal diameter Ø=D /mm/	Name	Manufacturing length /mm/	ID number
82	IZOTEX-A12	L=10 m	C05082
102	IZOTEX-A12	L=10 m	C05102
112	IZOTEX-A12	L=10 m	C05112
120	IZOTEX-A12	L=10 m	C05120
127	IZOTEX-A12	L=10 m	C05127
133	IZOTEX-A12	L=10 m	C05133
140	IZOTEX-A12	L=10 m	C05140
152	IZOTEX-A12	L=10 m	C05152
160	IZOTEX-A12	L=10 m	C05160
165	IZOTEX-A12	L=10 m	C05165
185	IZOTEX-A12	L=10 m	C05185
203	IZOTEX-A12	L=10 m	C05203
229	IZOTEX-A12	L=10 m	C05229
254	IZOTEX-A12	L=10 m	C05254
280	IZOTEX-A12	L=10 m	C05280
305	IZOTEX-A12	L=10 m	C05305
315	IZOTEX-A12	L=10 m	C05315
356	IZOTEX-A12	L=10 m	C05356
406	IZOTEX-A12	L=10 m	C05406
457	IZOTEX-A12	L=10 m	C05457
508	IZOTEX-A12	L=10 m	C05508