



DESCRIPTION

Material: Single layer aluminium stripwound flexible pipe of AL 99,5 resistant to moisture.

Application: Ventilation of wet environments. Due to transport and dimensional stability the pipe can be compressed to approx. 1/3 of its length.

🔥 **Application temperature:** od -30°C to +200°C 🔄 **Diameters:** 80mm to 400mm → **Manufacturing lengths:** max. 10m

✳️ **Operating pressure:** max. permissible 10.000 Pa 🎨 **Colour:** silver gray # **Ident:** C11+diameter

Internal diameter Ø=D / mm /	Name	Manufacturing length /mm/	ID number
80	AL	L=10 m	C11080
90	AL	L=10 m	C11090
100	AL	L=10 m	C11100
110	AL	L=10 m	C11110
120	AL	L=10 m	C11120
125	AL	L=10 m	C11125
130	AL	L=10 m	C11130
135	AL	L=10 m	C11135
140	AL	L=10 m	C11140
150	AL	L=10 m	C11150
160	AL	L=10 m	C11160
170	AL	L=10 m	C11170
180	AL	L=10 m	C11180
190	AL	L=10 m	C11190
200	AL	L=10 m	C11200
220	AL	L=10 m	C11220
250	AL	L=10 m	C11250
300	AL	L=10 m	C11300
315	AL	L=10 m	C11315
350	AL	L=10 m	C11350
400	AL	L=10 m	C11400